
Spec Sheet

SMD Power Inductors (NR series) NR4018T2R2M



Features

- Item Summary

2.2uH±20%, 1.44A, 4.0x4.0x1.8mm

- Lifecycle Stage
- Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 3500pcs


Products characteristics table

Inductance	2.2 uH ± 20 %		
Case Size (mm)	4.0x4.0		
Rated Current (max)	1.44 A		
Saturation Current (max)	2.7 A		
Temperature Rise Current (max)	1.44 A		
DC Resistance (max)	72 mΩ		
DC Resistance (typ)	60 mΩ		
LQ Measuring Frequency	100 kHz		
Self Resonant Frequency (min)	52 MHz		
Operating Temp. Range	-25 to +120 ℃ (Including-self-generated heat)		
Temperature characteristic (Inductance change)	± 20 %		
RoHS2 Compliance (10 subst.)	Yes		
REACH Compliance (173 subst.)	Yes		
Halogen Free	Yes		
Soldering	Reflow		

External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.8 mm
Dimension e	1.1 ±0.2 mm
Dimension f	2.5 ±0.2 mm

Recommended Land Patterns





The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the Date at any time without notice. Before making final selection, please check product specification. 2017.04.30


TAIYO YUDEN

SMD Power Inductors (NR series)

	Dimension	unit : mm	unit : inch
NR4018T2R2M	Length :	4.0 +/- 0.2	(0.157 +/- 0.008)
	Width :	4.0 +/- 0.2	(0.157 +/- 0.008)
	Height :	1.8 max	. (0.071 max.)
	Inductance :	2.2 uH	(test freq at 0.1MHz)
	DC Resistance :	0.06 / 0.07	2 ohm (typ / max)
	Saturation Current : 2,700 mA (max)		
	Temp. rise Current :	1,440 mA(n	nax)
	Saturation current	typical : 30% reduc	ction from initial L value.
	Temp rise Current	typical : Temperatu	ire will rise by 40 deg C







The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.